

10/56/081  
PCT/EP200 4 / 0 0 7 8 2 1



INVESTOR IN PEOPLE


The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



**CERTIFIED COPY OF  
PRIORITY DOCUMENT**

Signed

*W. Evans*


Dated 5 July 2004

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

An Executive Agency of the Department of Trade and Industry

**BEST AVAILABLE COPY**



14JUL03 E822169-6 002029  
P01/7700 0.00-0316345.8

**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office  
Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference	JNR/LTH/PB60389P- A	
2. Patent application number (The Patent Office will fill in his part)	0316345.8	11 JUL 2003
3. Full name, address and postcode of the or of each applicant (underline all surnames)  Patents ADP number (if you know it)  If the applicant is a corporate body, give the country/state of its incorporation	Glaxo Group Limited Glaxo Wellcome House, Berkeley Avenue, Greenford, Middlesex UB6 0NN, Great Britain  United Kingdom  473587003	
4. Title of the invention	A Dispenser	
5. Name of your agent (if you have one)  "Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)  Patents ADP number (if you know it)	Corporate Intellectual Property  GlaxoSmithKline Corporate Intellectual Property (CN9 25.1) 980 Great West Road BRENTFORD Middlesex TW8 9GS  8072555006	
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)      Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer yes if: . a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is named as an applicant, or c) any named applicant is a corporate body See note (d)		

**Patents Form 1/77**

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document

Continuation sheets of this form

Description

Claim(s)

Abstract

Drawings

18  
10 DL  
1  
100 W

10. If you are also filing any of the following, state how many against each item.

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(please specify)

11.

We request the grant of a patent on the basis of this application

Signature

J N Rice

Date 11-Jul-03

12. Name and daytime telephone number of person to contact in the United Kingdom

J N Rice 01279 644508

**Warning**

*After an application for a Patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission unless an application has been filed at least six weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

**Notes**

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- f) For details of the fee and ways to pay please contact the Patent Office.

**Patents Form 1/77**

A DISPENSER

Related Applications

5       The present application is related to the UK  
patent applications filed concurrently herewith by the  
Applicant (Glaxo Group Limited) under the title 'A  
Dispenser' and with Applicant's references PB60389P-B,  
PB60389P-C and PB60389P-D. The contents of these  
10 applications are hereby incorporated herein by  
reference.

Field of the Invention

15       The present invention relates to a dispenser for  
dispensing unit products, for instance pills, such as  
pharmaceutical pills. The term "pill" is meant to  
embrace tablets, capsules and the like, and other  
solid oral dosage forms, whether pharmaceutical or  
20 otherwise.

Summary of the Invention

      According to the present invention there is  
25 provided a dispenser according to claim 1 hereof.

      Other aspects and preferred features of the  
invention are set out in the other claims (including  
those in the related applications referred to above)  
30 and in the exemplary embodiment hereinafter to be

described with reference to the accompanying FIGURES of drawings.

Brief Description of the FIGURES of Drawings

5

FIGURE 1 shows a standard container for containing and dispensing pharmaceutical pills comprising a bottle and a lid.

10

FIGURE 2 shows a hand-held dispenser for pharmaceutical pills according to an embodiment of the present invention comprising the bottle and the lid of FIGURE 1 and a dispensing module, the dispensing

15

module being mounted on the bottle and the lid being mounted on the dispensing module.

FIGURE 3 shows the dispenser without the lid.

20

FIGURES 4A and B are side views of the dispensing module.

FIGURE 5 is an exploded view of the dispensing module.

25

FIGURES 6A-C are perspective end views of the dispensing module showing how a battery can be replaced.

30

FIGURES 7A-E are longitudinal sectional views of the dispensing module illustrating its operation to

dispense a pill therefrom and showing the internal channel structure of the module.

FIGURES 8A and B are schematic views of the  
5 channel structure in the dispensing module.

FIGURES 9A-C are schematic views illustrating the dispensing of a pill from the dispensing module.

10 FIGURES 10-C correspond to FIGURES 9A-C, but show the inclusion of switches to control operation of an electronic dose counter of the dispensing module.

FIGURE 11 shows the dispenser being pressed  
15 against a user's palm to "blot" out a pill therefrom.

FIGURE 12 shows a display of the electronic dose counter illustrating the segmented nature thereof.

20 Detailed Description of the FIGURES of Drawings

In the FIGURES of drawings there is shown a hand-held dispenser 1 of the invention for dispensing pills 3, in this embodiment pharmaceutical pills. The  
25 dispenser has a container or bottle 100, a lid 200 and a dispensing module 300 releasably mountable on the bottle 100.

Referring to FIGURE 1, the bottle 100 in this  
30 embodiment is of standard pill bottle construction, having a hollow body 101 which is formed with a base

103, on which the dispenser 1, when assembled, is able to stand upright, and a neck 105, through which an access opening 107 is provided to the internal volume of the body 101 in which the pills 3 are contained.

- 5 The access opening 107 is sized so as to enable the pills 3 to be tipped out of the bottle 100 when oriented upside down.

The body 101 is preferably formed from a plastics material or glass. The plastics material may be a polyethylene, for instance low density polyethylene (LDPE), or polypropylene (PP), for example.

15 The neck 105 has an outer circumferential surface 109 on which is provided a screw thread profile 111.

The lid 200, which is preferably of a plastics material, has an annular skirt 201 which depends from an end wall 203. The annular skirt 201 has an inner circumferential surface on which is provided a screw thread profile (not shown) which is complementary to the screw thread profile 111 on the bottle neck 105. In this way, the lid 200 is able to be screwed onto the bottle neck 105 to sealingly close the access opening 107. Preferably, the screw fitting between the bottle 100 and the lid 200 is of a child-resistant nature, i.e. a force additional to turning is needed to remove the lid 200 from the bottle 100. As examples, there may be mentioned "squeeze-and-turn" and "push-and-turn" closures.

Of course, other types of co-operable connection structures on the bottle 100 and lid 200 could be used, again preferably being of a child-resistant type, namely requiring two different types of force to be applied for removal of the lid 200 from the bottle 100.

As shown in FIGURES 2-7, the dispensing module 300 has a hollow body 301, which is preferably of a plastics material, having a lower end 303 and an upper end 305. The body 301 has an internal cavity 307 to which there is provided a lower opening 309 in the lower end 303, and an upper opening 311 in the upper end 305.

The lower end 303 defines an annular skirt 313 about the lower opening 309 having an inner circumferential surface 315 on which is provided a first screw thread profile 317 complementary to the screw thread profile 111 on the bottle neck 105. Thus, the dispensing module 300 is able to be screw mounted onto the bottle neck 105, in similar fashion to the lid 200. The first screw thread profile 317 may form a child-resistant connection with the bottle neck screw thread profile 111, and is conveniently identical to the lid screw thread profile.

At the module upper end 305 there is located a nozzle 319 of tubular form having a lumen 321 which defines the upper opening 311. The nozzle 319 is arranged for sliding movement in the dispensing module



300 along its longitudinal axis. A spring or other biasing mechanism 320 (see FIGURE 5) is provided to bias the nozzle 319 outwardly to a rest position, as shown in FIGURES 2-4, for example.

5

The nozzle 319 has an outer circumferential surface 323 on which is provided a second screw thread profile 325 of the dispensing module 300. The second screw thread profile 325 is complementary to the lid screw thread profile thereby enabling the lid 200 to be screwed onto the nozzle 319 when in its rest position to close the upper opening 311, as shown in FIGURE 2. Moreover, when the lid 200 is mounted on the nozzle 319, the nozzle 319 is unable to be slid inwardly from its rest position through abutment of the lid skirt 201 with an annular shoulder 327 of the dispensing module body 301.

Again, the second screw thread profile 325 preferably co-operates with the lid screw thread profile to form a child-resistant connection. Conveniently, the second screw thread profile 325 is identical to the screw thread profile 111 on the bottle neck 105.

25

It will therefore be seen that the dispenser 1 enables the lid 200 to be replaced on the bottle 100 by the dispensing module 300 and then in turn mounted on the nozzle 319 to close the upper opening 311 of the module 300 (the "assembled state"). Thus, the dispensing module 300 can be mounted on a standard

30

pill bottle and be closed by the lid for the standard bottle. This is shown in FIGURE 2.

As shown in FIGURES 6-8, the module internal cavity 307 has a funnel-like configuration, having a cylindrical entrance 329 at the lower opening 309, with tapered sides 330, and a generally rectangular slot 331, which extends towards the upper opening 311 through the lumen 321 of the nozzle 319.

10

As shown in FIGURES 7 and 8, the slot 331 has a lower section 332 of a first width  $w_1$ , which is greater than the diameter  $pd$  of the pills 3, and an upper section 334 of a second width  $w_2$  less than the first width  $w_1$ , but greater than the pill diameter  $pd$ , but less than twice the pill diameter  $pd$ . The upper slot section 334 is offset to the lower slot section 332. Moreover, the lower slot section 332 has a base surface 336 which tapers in the upward direction.

20

When the dispenser 1 is inverted in its assembled state, the pills 3 are gravity fed from the bottle 100 into the dispensing module 300 through the communicating access and lower openings 107, 309. The pills 3 so transferred into the dispensing module 300 are funnelled firstly by the tapered sides 330 into the lower slot section 332. In this regard, the tapered sides 330 act to funnel the pills 3 into the slot 331 in the same predetermined orientation. In this embodiment, the pills 3 are circular and funnelled into the slot 331 in a radial orientation so

30

that they are arranged circumference-to-circumference in the slot 331.

5       The pills are then gravity fed into the upper slot section 334 by the tapered base surface 336 of the lower slot section 332. In this way, a single-line queue 333 of pills 3 is formed in the upper slot section 334, as shown in FIGURE 7, for example.

10       Preferably, the lower and upper slot sections 332,334 have dimensions relative to the pills 3 as shown in FIGURES 8A-B. That is to say, the lower slot section 332 preferably has a depth  $d_1$  from its entrance to the side edge of the tapered base surface  
15 336 which is greater than 1.5 times the pill diameter  $p_d$ . Furthermore, the upper slot section 334 preferably has a depth  $d_2$  which is less than the pill diameter  $p_d$ , but greater than the pill width  $p_w$ . This enables dispensing of the pills 3 to occur while preventing or  
20 inhibiting the pills jamming and disabling operation. It allows pills 3 already in the dispensing module 300 to move down the slot 331 even when pills 3 are blocking the entrance 329.

25       As will now be described with reference to FIGURES 7, 9 and 10, the dispensing module 300 has a dispensing mechanism 350 which is actuatable to dispense one pill 3 from the upper opening 311 per actuation. In this embodiment, the nozzle 319 forms the actuator  
30 of the dispensing mechanism 350. The dispensing mechanism 350 further has a gate 351 comprising a

movable part 353 carried by the lumen 321 of the nozzle 319, and a stationary part 355 in front of the slot 331.

5       The movable part 353 comprises a first switch member 357 on a first side of the nozzle lumen 321, and a guide member 359 on the opposite side of the nozzle lumen 321. The first switch member 357 is arranged so as to slide over the outer surface of the  
10 upper slot section 334 when the nozzle is depressed, whereas the guide member 359 is arranged so as to slide inside the upper slot section 334.

      The first switch member 357 has a resilient arm  
15 358 which is biased to an outboard rest state. This is the open state of the first switch member 357. The guide member 359, on the other hand, has a curved guide surface 360 which, in the rest position of the nozzle 319, forms an extension of a side wall 340 of  
20 the upper slot section 334 at the outlet end thereof.

      As shown in FIGURE 7E, for example, the stationary part 355 comprises a side extension 361 of the upper slot section 334 and a finger 363 which  
25 extends from the side extension 361 transversely to the slot axis and which is spaced from the outlet end of the upper slot section 334 by a distance at least equal to the pill diameter pd. Moreover, the finger 363 is offset to the slot axis on the same side of the  
30 axis as the first switch member 357.

When the nozzle 319 is in its outboard, rest position, the movable and stationary parts 353,355 cooperate to form a barrier across the upper opening 311, i.e. the gate 351 is closed. This is shown in 5 FIGURES 7A, 9A and 10A. More particularly, the guide surface 360 ends adjacent the finger 363 on one side thereof, and the switch arm 358 is in its rest state disposed adjacent the finger 363 on the other side.

10 As mentioned previously, when the dispenser 1 is inverted, a queue 333 of pills 3 forms in the slot 331. As will be appreciated from FIGURES 7A, 9A and 10A, the pill 3 at the front of the queue (hereinafter the "leading pill") passes out of the slot 331 and 15 slides down the guide surface 360 and comes to rest on the finger 363 and against the switch arm 358. The other pills 3 in the queue 333 are stacked-up behind the leading pill offset thereto.

20 As shown in FIGURES 7, 9 and 10, in order to dispense the leading pill 3 of the queue 333 from the dispenser 1, the nozzle 319 is depressed inwardly. This results in the switch and guide members 357,359 moving inwardly. As the first switch member 357 moves 25 inwardly, the switch arm 358 closes through its interaction with the leading pill 3. In this relation, the guide surface 360 may have a camming action which pushes the leading pill 3 sideways against the switch arm 358. Eventually, a gap 367 is 30 formed between the first switch member 357 and the finger 363 large enough for the leading pill 3 to fall

out of the nozzle 319 (see FIGURES 7E, 9C and 10C). In other words, the gate 351 has been opened.

As shown in FIGURE 11, a pill 3 can be dispensed in this manner by a user pushing the nozzle 319 into their palm. Such action causes the leading pill 3 to be "blotted" out of the dispenser 1 into the palm as the nozzle 319 is slid inwardly from its rest position to actuate the dispensing mechanism 350. This action is natural and a logical progression from the tipping out of pills from a conventional pill bottle.

As further shown in FIGURES 7D, 7E, 9C and 10C, inward movement of the nozzle 319 not only causes the leading pill 3 to be dispensed, but causes the guide member 359 to push the remaining pills 3 in the queue 333 inwardly as well. This action helps to free pills 3 which would otherwise jam the dispensing module 300.

Return of the nozzle 319 to its rest position closes the gate 351 in preparation for the next dispensing cycle.

It will therefore be understood that the dispenser 1 has a dispensing mechanism 350 which operates to dose one pill 3 from the dispenser 1 per actuation.

From FIGURE 5 it will be seen that the dispensing module 300 is formed from an assembly of component parts, predominantly of a plastic material. More

particularly, the module 300 has an outer casing 370, which provides the first screw thread profile 317, an inner insert 375, which co-operates with the outer casing 370 to define the funnel-like channel configuration, an outer insert 380 which presents the nozzle 319 and is slidably mountable in the outer casing 370 for sliding movement relative to the inner insert 375, and a collar 385 fixable to the outer casing 370 which presents an aperture 387 behind which the electronic display 401 is disposed.

As shown in FIGURES 2-6 and 11, the dispensing module 300 is further provided with an electronic dose counter 400, having a circular electronic visual display 401, preferably a liquid crystal display (LCD), on which is numerically displayed the number of pills 3 contained in the dispenser 1. After each dispensing cycle, the counter 400 decrements the number displayed on the display 401 by one.

The electronic counter 400 is powered by a battery 402, e.g. a 3 volt CR2016 lithium cell or similar capacity variant, and has a printed circuit board (PCB) 403 on which is mounted a microcontroller (not shown), e.g. an Epson S1C60N16, and other appropriate electronic componentry, as will be understood by the skilled person in the art. The microcontroller is programmed to control the number displayed on the display 401, and in this connection may be connected to the display 401 through an elastomer, such as a flexible heat-seal connector.

Moreover, the microcontroller is electrically connected to the first switch member 357 forming part of the gate 351 and also to a second switch member 367 carried by the nozzle 319 (FIGURES 10A-C).

5

Thus, the microcontroller receives a first electrical input signal when the resilient arm 358 of the first switch member 357 is closed as it interacts with the leading pill 3 as the nozzle 319 is depressed. In other words, the first input signal is indicative that a pill 3 has passed the first switch member 357 and has been dispensed. Alternatively, the first switch member 357 may be configured such that it is closed, and hence produces the first input signal, when the gate 351 is closed. For instance, by the leading pill 3 bearing against the switch arm 358 when the dispenser 1 is inverted.

The second switch member 367 also has a resilient arm 369. The resilient arm 369 of the second switch member 367 is biased to an open position, but when the nozzle 319 is actuated it abuts an internal surface 371 of the nozzle 319 (FIGURES 10A-C) causing it to close. This results in a second electrical input signal being received by the microcontroller, which signal is representative of the nozzle 319 have been depressed a sufficient amount to effect dispensing (i.e. actuated).

Thus, the microcontroller receives two input signals, each independently indicating dispensing.



Both signals are required to be received by the microcontroller for it to act to decrement the number on the display 401. This is because the first input signal indicates the presence of a pill 3 (the leading pill) at the gate 351 due to its dependence on a pill triggering the first switch member 357, while the second input signal represents full travel of the nozzle 319 which should ensure dispensing of the pill 3 detected by the first switch member 357. This provides a fail-safe mode of counting.

When the dispenser 1 is first used, the microcontroller is programmed to display the "label claim" of pills contained therein. This may be a factory setting, or set by the prescribing medical practitioner or pharmacist. Each time the dispenser 1 is actuated, and the microcontroller receives the two input signals, which may be required to be simultaneously received or, more likely, sequentially (i.e. the first switch member 357 re-opens before the second switch member 367 closes), perhaps within a specified time period, it operates to cause the electronic display to decrement the number displayed by one. There may also be a requirement that both switches 357,367 need to be re-opened for the microcontroller to update the display 401. That is to say, the microcontroller is programmed or configured such that it will only operate to decrement the count when the two input signals are not only received, but switched-off by the switches re-opening. This adds a further fail-safe.

Of course, the dispenser 1 could be operated with just one of the switch members 357,367. For instance, as represented in FIGURE 7, only the first switch  
5 member 357 may be included in the dispenser 1.

Eventually, the display 401 will record that no pills 3 are left. In this regard, the microcontroller may be programmed to cause the display 401 to flash  
10 when the number of pills left is at or below a predetermined threshold to warn the user that a new supply of pills is, or will shortly be, needed. As an example, the microcontroller may operate to cause the display to flash the number displayed. The display  
15 401 may flash when the number displayed is zero.

In addition to the counter function, the microcontroller and electronic display are also operatively connected such that a 'time since last  
20 dose' function is displayed by the display 401. This is particularly useful when the pills 3 are pharmaceutical pills.

As shown in FIGURE 4A, about the circumference  
25 407 of the display 401 there is provided a scale 409 representing the time since a pill was last dispensed, in this instance each section between the adjacent indicia 411 of the scale 409 representing six hour periods, although, of course, other time periods could  
30 be represented.

After the microcontroller registers the dispensing of a pill 3 through triggering of the first and second switches 357,367, a timer in the microcontroller is activated and at predetermined intervals thereafter discrete time segments 413 are displayed on the display 401 adjacent the scale 409. In this embodiment each time segment 413 represents two hour periods, although again other time periods could be represented. Thus, after two hours from last dispensing, a first time segment 413 is displayed in the first section of the scale. This is repeated after each further two hour period until another pill is dispensed to re-set the 'time since last dose' function. Preferably, as each new time segment 413 is displayed, the previous time segments 413 remain resulting in a time segment chain being formed.

The user of the dispenser 1 will know the dosing regime for the pills 3 (i.e. the time interval between pill taking), either from the prescribing medical practitioner, pharmacist or information leaflet packed with the dispenser 1, and is provided with a visible indication of the time left till the next pill dose is needed, or of the lateness of the next dose. Thus, the dispenser 1 aids in compliance of the user in following the prescribed dosing regime. If need be, the microcontroller can be pre-programmed to cause the display to flash when the time since the last dose corresponds to the prescribed dosing regime, e.g. by flashing the time segments and/or the number of pills left.

A preferred display 401 for the dispenser 1 is shown in FIGURE 12. As will be seen, the display 401 is a segmented display, having a plurality of independently activatable segments, including the circumferentially-arranged time segments 413 for the 'time since last dose' function. In addition, the display 401 has a pair of seven-segment number-forming display sections 415.

10

FIGURES 6A-C show the sequence of steps for removing the battery 402 from the dispensing module 300 for replacement with a new battery. More particularly, the battery is held in a battery holder 425 having a recess 427 for accommodating the battery 402. The battery holder 425 is slidably mounted into a slot 429 formed in the tapered side 330 in the cylindrical entrance 329 at the lower module opening 309. To this end, the battery holder 402 has a tapered surface 431 so that, when slid into the slot 429, it sits flush with the tapered side 330. To remove the battery holder 425 to replace the battery 402, a screw driver or other like implement is used to lever the battery holder 425 out of the slot 429.

25

By enabling the battery 402 to be replaced enables the dispensing module 300 to be re-usable. Nonetheless, the dispensing module 300 may be configured such that the battery 402 is not able to be removed, e.g. in the event the module 300 is designed

30

to be a single-use component which is to be disposed of after use.

For tamper-proofing of the dispenser 1, a label  
5 500 can be wrapped around the dispenser 1 so as to  
cover the bottle and the dispensing module 300, as  
shown in FIGURE 2. As will be appreciated, if the  
bottle 100 and dispensing module 300 are disconnected  
this will damage the label 500 since this bridges the  
10 joint between the bottle 100 and the dispensing module  
300. This is particularly advantageous where the  
dispensing module 300 has a re-set button or the like  
for re-setting the dose counter back to the "label  
claim" which is only accessible when the module 300 is  
15 free of the bottle 100.

It will be appreciated that the invention is not  
limited to the exemplary embodiment herein described  
with reference to the accompanying FIGURES of  
20 drawings, but may be modified, varied and adopt other  
guises within the scope of the appended claims. As an  
example, the dispenser need not have a counter. For  
example, FIGURES 9A-C show a dispensing mechanism  
which does not rely on a switch member.

CLAIMS

1. A hand-held dispenser for dispensing a multiplicity of unit products comprising:-
  - 5 a container for containing the unit products which has an access opening through which the unit products are able to be removed from the container; and
  - 10 a dispensing module which is adapted to be connected to the container in an operational position in which the dispensing module covers the access opening, the dispensing module having:-
    - 15 an internal volume into which the unit products are transferable from the container through the access opening when the dispensing module is in the operational position;
    - an outlet opening which communicates with the internal volume; and
    - 20 a dispensing mechanism which operates to dispense a predetermined number of unit products from the outlet opening on actuation thereof.
2. The dispenser of claim 1 further having a closure for closing the outlet opening.
- 25 3. The dispenser of claim 2 wherein the closure is able to close the access opening of the container.
4. The dispenser of claim 2 or 3 wherein the closure is a cap.
- 30

5. The dispenser of claim 2, 3 or 4 wherein the closure is adapted to be releasably fitted to the dispensing module and/or the container.

5 6. The dispenser of claim 5 wherein the closure is able to be screw fitted to the dispensing module and/or the container.

7. The dispenser of any one of the preceding  
10 claims in which the dispensing mechanism is adapted in use to dispense the unit products one at a time from the outlet opening.

8. The dispenser of any one of the preceding  
15 claims in which the predetermined number is one.

9. The dispenser of any one of the preceding claims wherein the dispensing mechanism is manually actuable by a user.

20

10. The dispenser of any one of the preceding claims wherein the dispensing mechanism has a non-dispensing mode, in which it prevents the unit products from being dispensed from the outlet opening,  
25 and a dispensing mode, in which it dispenses the predetermined number of unit products from the outlet opening, the dispensing mechanism moving from the non-dispensing mode to the dispensing mode on actuation of the dispensing mechanism.

30

11. The dispenser of claim 10 wherein the dispensing mechanism is biased to the non-dispensing mode by a biasing structure in the dispensing module.

5 12. The dispenser of any one of the preceding claims wherein the dispensing mechanism has a gate mechanism which moves from a shut state to an open state on actuation of the dispensing mechanism, the gate mechanism shutting the outlet opening in the shut  
10 state to prevent dispensing of the unit products therefrom and opening the outlet opening in the open state to enable dispensing of the unit products therefrom.

15 13. The dispenser of any one of the preceding claims wherein the dispensing mechanism is adapted to cause the unit products to be conveyed to the outlet opening one at a time.

20 14. The dispenser of claim 13 wherein the dispensing module internal volume has a channel along which the unit products are conveyable to the outlet opening, the channel adapted to cause the unit products to be conveyed to the outlet opening one at a  
25 time.

15. The dispenser of any one of the preceding claims wherein the dispensing mechanism is adapted to cause the unit products to be conveyed to the outlet  
30 opening in a common predetermined orientation of the unit product.



16. The dispenser of claims 14 and 15 wherein the channel is further adapted to cause the unit products to be conveyed to the outlet opening in the  
5 common predetermined orientation.

17. The dispenser of claim 14 or 16 wherein the internal volume defines a funnel-like shape which comprises the channel at an outlet end thereof and a  
10 mouth of tapered construction at an inlet end thereof which communicates with the container access opening in the operational position of the dispensing module and operates in use to funnel the unit products into the channel.

15 18. The dispenser of claim 14, 16 or 17 wherein the channel is of length sufficient that a queue of unit products is able to form therein.

20 19. The dispenser of any one of claims 14 or 16 to 18 when appendant on claim 12 wherein the gate mechanism blocks the channel in its shut state and unblocks the channel in its open state.

25 20. The dispenser of claims 18 and 19 wherein the gate mechanism is adapted to selectively release the predetermined number of unit products at the front of the queue when moved to its open state.

30 21. The dispenser of claim 20 wherein the gate mechanism is adapted such that in its shut state it

blocks the channel in front of the queue and such that when it is moved from the shut state to the open state it unblocks the channel in front of the queue and blocks the channel behind the predetermined number of  
5 unit products at the front of the queue whereby the predetermined number of unit products is dispensed from the outlet opening.

22. The dispenser of claim 21 wherein the gate  
10 mechanism is further adapted such that as it moves from the shut state to the open state it displaces the portion of the queue disposed behind the predetermined number of unit products at the queue front backwards in the channel.

15 23. The dispenser of any one of the preceding claims in which the dispensing mechanism has a manually-engagable actuator for actuating the dispensing mechanism.

20 24. The dispenser of claim 23 wherein the actuator protrudes from the dispensing module and is displaceable to actuate the dispensing mechanism.

25 25. The dispenser of claim 24 wherein the actuator is displaceable into the dispensing module.

26. The dispenser of claim 23, 24 or 25 wherein the actuator and outlet opening are so arranged on the  
30 dispensing module that the actuator is able to be

actuated by a hand of a user so that the predetermined number of unit products is dispensed into that hand.

27. The dispenser of claim 26 wherein the  
5 actuator and outlet opening are provided in a surface of the module such that pushing the module surface into a user's palm is able to cause actuation of the actuator and dispensing into the palm.

10 28. The dispenser of any one of claims 23 to 27 when appended directly or indirectly on claim 12 in which the actuator forms at least a part of the gate mechanism.

15 29. The dispenser of any one of the preceding claims including the unit products.

30. The dispenser of any one of the preceding claims in which the unit products are pharmaceutical  
20 products.

31. The dispenser of claim 30 wherein the pharmaceutical products are oral dosage forms.

25 32. The dispenser of any one of the preceding claims in which the dispensing module further has a dispensing indicator which is adapted in use to indicate the number of unit products dispensed from, or remaining in, the dispenser.

33. The dispenser of claim 32 wherein the dispensing indicator has a display which in use represents graphically the number of unit products dispensed or remaining.

5

34. The dispenser of claim 33 in which the dispensing indicator is a counter and the display in use represents numerically the number of unit products dispensed or remaining.

10

35. The dispenser of claim 33 or 34 wherein the display is an electronic display.

36. The dispenser of any one of claims 32 to 35 in which the dispensing indicator is an electronic indicator.

15

37. The dispenser of any one of claims 32 to 36 wherein the dispensing indicator is operatively coupled to a detector which is adapted in use to detect actuation of the dispensing mechanism.

20

38. The dispenser of any one of claims 32 to 37 wherein the dispensing indicator is operatively coupled to a detector which is adapted in use to detect dispensing of the predetermined number of unit products.

25

39. The dispenser of claim 37 or 38 when appended directly or indirectly to claim 35 wherein the dispensing indicator has an electrical control

30

circuit for controlling the display and the  
detector(s) is a trigger(s) for the circuit.

40. The dispenser of claim 39 wherein the  
5 trigger(s) is a switch operable to trigger the  
circuit.

41. The dispenser of claim 40 when appended to  
claim 37 wherein the dispensing mechanism is adapted  
10 to operate the switch when actuated.

42. The dispenser of claim 40 when appended to  
claim 38 wherein the switch is positioned so as to be  
operated by the unit product(s).

15 43. The dispenser of any one of the preceding  
claims in which the dispensing module has a timing  
mechanism adapted in use to time the period since last  
dispensing of the predetermined number of unit  
20 products.

44. The dispenser of claim 43 in which the  
timing mechanism is adapted in use to indicate the  
time since last dispensing.

25 45. The dispenser of claim 44 having a display  
on the dispensing module forming part of the timing  
mechanism on which, in use, the time since last  
dispensing is graphically indicated thereon.

30

46. The dispenser of claim 43, 44 or 45 wherein the timing mechanism has a controller programmed with a predetermined dispensing regime for dispensing of the unit products and the controller controls the timing mechanism so that it provides an alert when dispensing of the unit products is required in accordance with the dispensing regime.

47. The dispenser of any one of the preceding claims which is adapted such that in use the unit products are gravity-fed from the container to the dispensing module.

48. The dispenser of claim 47 which is adapted such that in use the unit products are gravity-fed to the outlet opening.

49. The dispenser of any one of the preceding claims in which the dispensing module is connected to the container and a tamper-evidence structure is provided to show whether the dispensing module is subsequently disconnected from the container.

50. The dispenser of claim 49 in which the tamper-evidence structure is applied across a boundary between the dispensing module and the container.

51. The dispenser of claim 50 wherein the tamper-evidence structure is a label.

52. The dispenser of any one of the preceding claims wherein the dispensing mechanism is a pump-based mechanism.

5 53. A dispensing module for connection to a container for unit products as set forth in any one of the preceding claims.

54. The dispensing module of claim 53 having a  
10 first connector structure for connecting the dispensing module to the container and a second connector structure for enabling connection of a closure to the dispensing module to close the outlet opening, the first and second connector structures  
15 being complementary to one another whereby the closure is also connectable to the container in place of the dispensing module.

55. A dispenser for dispensing a multiplicity of  
20 unit products substantially as hereinbefore described with reference to, and illustrated in, FIGURES 2-12 of the accompanying drawings.



56. A dispensing module for connection to a  
25 container for unit products substantially as hereinbefore described with reference to, and illustrated in, FIGURES 2-12 of the accompanying drawings.

A DISPENSERAbstract

5       A hand-held dispenser (1) for dispensing a  
multiplicity of unit products (3) comprises a  
container (100) for containing the unit products which  
has an access opening (107) through which the unit  
products are able to be removed from the container and  
10   a dispensing module (300) which is adapted to be  
connected to the container in an operational position  
in which the dispensing module covers the access  
opening. The dispensing module has an internal volume  
(307), into which the unit products are transferable  
15   from the container through the access opening when the  
dispensing module is in the operational position, an  
outlet opening (311) which communicates with the  
internal volume, and a dispensing mechanism (350)  
which operates to dispense a predetermined number of  
20   unit products from the outlet opening on actuation  
thereof.

(FIG. 3)





2/10




FIG. 3

3/10




FIG. 4A





FIG. 4B

4/10






FIG. 6

6/10









FIG. 7


$$d2 < p_d$$


$$D2 > p_w$$

FIG. 8A




FIG. 8B

8/10





9/10



10/10



FIG. 11




FIG. 12

**THIS PAGE BLANK (USPTO)**

*Dmt*  
**PCT/EP2004/007821**



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**